



SPECIFICATIONS

- 1- FREQUENCY - AS NOTED
- 2- VSWR 1.10:1 MAX.
- 3- POWER HANDLING PER TABLE 1
- 4- PRESSURIZATION 10 PSIG
- 5- ENVIRONMENT OUTDOORS
- 6- TEMPERATURE -40 TO 60 DEGREES C
- 7- MATERIAL - BRASS OR ANODIZED ALUMINUM
- 8- TOLERANCES (UNLESS OTHERWISE SPECIFIED)
 - 2 PLACES +/- 0.020 INCHES
 - 3 PLACES +/- 0.005 INCHES

TABLE 1

P/N	W/G	FLANGE	FREQ (GHZ)	POWER MAX
2146-0000-1	WR75	CPRF/CPRF	10-15.2	2.2 KW
2146-0000-2	WR75	CPRG/CPRF	10-15.2	2.2 KW
2639-0000-1	WR112	CPRG/CPRF	7.05-10.0	2.8 KW
2114-0000-1	WR137	CPRG/CPRF	5.850 TO 6.425	3.5 KW
2114-0000-2	WR137	CPRF/CPRF	5.850 TO 6.425	3.5 KW
2145-0000-1	WR159	CPRG/CPRF	5.850 TO 6.425	3.5 KW
2145-0000-2	WR159	CPRF/CPRF	5.850 TO 6.425	3.5 KW
2340-0000-1	WR229	CPRF/CPRF	3.4 TO 4.9	3.5 KW
2340-0000-2	WR229	CPRG/CPRF	3.4 TO 4.9	3.5 KW
2707-0000-1	WR284	CPRG/CPRF	2.60 TO 3.95	2.0 KW
2707-0000-2	WR284	CPRG/CPRG	2.60 TO 3.95	2.0 KW

Microwave Components and Systems
583 Berlin Road, Marlboro MA

CPR FLANGE PRESSURE WINDOWS

DRAWING NO.

SEE TABLE

REV

-